



AMP2060CCF

20"x16"x10" POLYLINEÆ polycarbonate wall mount enclosure assembly with 4-screw lift-off clear cover

Availability:

In-Stock (Normally ships within 2-4 business days after receipt of order) – Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate **Closure Type:** 4-Screw Lift-Off

Mounting Description: Nonmetal flange fastened to

back side brass insert

Height: 19.76 in **Width:** 15.43 in **Depth:** 10 in

Usable Depth: 9.95 in **Volume:** 3200 cu in

Product Info

Brand: POLYLINE®

UPC: 85339985655

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 16 lbs

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear cover

Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)

2. RoHS directive



