ISSUE DATE: 6.72 170.69 → .56[14.30] → 3.99 101.22 .88[22.23]-OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS -(4) POLYCARBONATE FEET .10 [2.54] **BACK VIEW** 6.50 165.10 4.10 104.14 (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS STEEL FLANGE AND **FEET SCREWS** 7.47 [189.68] 5.20 131.98 STAINLESS STEEL 6.75 [171.44] **HINGE PIN** (4) \emptyset .31 [7.95] FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-NEOPRENE → 4.91 [124.65] < NONMETALLIC → 4.81 [122.24] < LOCKABLE SNAP LATCH **GASKET** LOCATED ON CENTER 6.04 [153.40] 4.81 [122.24] - .13 [3.30] 4.25 [107.95] MUTON PATE INC. (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664CCNL THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED CLEAR COVER AND WINDOWS- POLYCARBONATE WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.