ISSUE DATE: .56 [14.30] - 6.72 [170.69] -3.99 [101.22] OPTIONAL BACK PANEL SHOWN
0.100 [2.54mm] TH'K- ALUMINUM
0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED
0.125 [3.18mm] TH'K- FIBERGLASS .76 [19.41] -В (4) POLYCARBONATE FEET 6.50 [165.10] .10 [2.54] 3.50 [88.90] (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS 3.99 [101.32] **BACK VIEW** STEEL FLANGE AND **FEET SCREWS** 5.20 [131.98] 7.47 [189.68] 3.50 [88.90] 6.75 [171.44] STAINLESS STEEL **HINGE PIN** (2) EACH #10-32 BRASS INSERTS AND STAINLESS STEEL CAPTIVE COVER SCREWS (4) \emptyset .31 [7.95] -FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-NEOPRENE → 4.91 [124.65] < → 4.81 [122.24] < **GASKET** - .13 [3.30] 6.04 [153.40] 4.81 [122.24] 4.25 [107.95] MUSEL PRINTING (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664HW THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED CLEAR COVER AND WINDOWS- POLYCARBONATE

WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.