SLIDER STYLE DISCONNECT TERMINAL BLOCKS

HIGHLIGHTS

FEATURES

- Slider Style Disconnect Terminals
  - **CDTTU** - Standard Slider Disconnect
  - **CDTTU-SH** - Double Disconnect Terminal
  - **CDTTUFT** - Same profile Feed-Through
- Specially designed socket headed screws act as fast monitoring points
- Disconnect is achieved by operating sliding link with screw driver

APPLICATIONS

- Disconnect & Test Applications

	CDTTU	**CDTTU-SH**	**CDTTUFT**
			
	Slider Disconnect Terminal	Slider Double Disconnect Terminal	Feed Through Terminal Slider Disconnect Profile
Dimensions & Weight			
Width	**8 mm**	**16 mm**	**8 mm**
Length	63 mm	63 mm	63 mm
Height w DIN Rail 35 x 7.5 mm	58.7 mm	58.7 mm	58.7 mm
Height w DIN Rail 35 x 15 mm	65.7 mm	65.7 mm	65.7 mm
Weight per piece	28.5 g	59.2 g	27.1 g
Technical Data/Ratings			
Approvals	cULus E220514 / CSA / IEC 60947-7-1	cULus E220514 / CSA / IEC 60947-7-1	cULus E220514 / CSA / IEC 60947-7-1
Wire Size (solid / stranded)	**16-8 AWG** / 1.5-10 mm²	16-8 AWG / 16-8 AWG / 1.5-10 mm²	**16-8 AWG** / 1.5-10 mm²
Voltage Rating	600 V / 800 V	300 V / 300 V / 160 V	600 V / 800 V
Current Rating	41 A / 57 A	25 A / 25 A / 10 A	41 A / 57 A
Torque	14 lb-in / 1.2 Nm	14 lb-in / 14 lb-in / 1.2 Nm	14 lb-in / 1.2 Nm
Insulation Material	Polyamide 66	Polyamide 66	Polyamide 66
Installation Instructions			
Wire Stripping Length	12 mm	12 mm	12 mm
Screwdriver	Flat Head 1.0 x 5.5 mm	Flat Head 1.0 x 5.5 mm	Flat Head 1.0 x 5.5 mm

Terminal Blocks	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Grey (standard)	**CDTTU**	50	**CDTTU-SH**	20	**CDTTUFT**	50
Red R	CDTTU/R	50	CDTTU-SH/R	20	CDTTUFT/R	50
Blue BU	CDTTU/BU	50	CDTTU-SH/BU	20	CDTTUFT/BU	50
Black BL	CDTTU/BL	50	CDTTU-SH/BL	20	CDTTUFT/BL	50
Orange O	CDTTU/O	50	CDTTU-SH/O	20	CDTTUFT/O	50
Green G	CDTTU/G	50	CDTTU-SH/G	20	CDTTUFT/G	50
Yellow Y	CDTTU/Y	50	CDTTU-SH/Y	20	CDTTUFT/Y	50
White W	CDTTU/W	50	CDTTU-SH/W	20	CDTTUFT/W	50

Accessories	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCDTTU	50	EPCDTTU	50	EPCDTTU	50
DIN Rail 32mm 35mm	2511120	20	2511120	20	2511120	20
DIN Rail 35mm	CA701-15/S	20	CA701-15/S	20	CA701-15/S	20
DIN Rail 35mm	2511160	10	2511160	10	2511160	10
End Stop	CA702	50	CA702	50	CA702	50
End Stop	CA802	50	CA802	50	CA802	50
End Stop	CA202	25	CA202	25	CA202	25
Shorting Plug 2 pole	QJ8/2	25	QJ8/2	25	QJ8/2	25
External Jumper 2 pole	CA710/2	100	CA710/2	100	CA710/2	100
External Jumper 3 pole	CA710/3	50	CA710/3	50	CA710/3	50
External Jumper 4 pole	CA710/4	50	CA710/4	50	CA710/4	50
External Jumper 10 pole	CA710/10	20	CA710/10	20	CA710/10	20
Shorting Plug	QJ8/2	25	–	–	QJ8/2	25
Marking Tag	MT8	1 Pk. (100 tags)	MT8	1 Pk. (100 tags)	MT8	1 Pk. (100 tags)

Altech Corp.® • 35 Royal Road • Flemington, NJ 08822-6000 • Phone (908)806-9400 • FAX (908)806-9490