

10x9x4 NEMA 4X Polycarbonate + ABS Weatherproof Enclosure



Features

- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Loops
- Optional Pole Mount Kit Available



Description

Weatherproof Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP100904** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

Complete with Cable Glands and Wire Management Accessories

This enclosure includes 4 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Pole Mount Available

A pole mounting kit is also available for this enclosure. It attaches to the rear of the enclosure and allows it to be mounted to poles and fence posts up to 9.5 inches in diameter.

Specifications

| Material | Polycarbonate + ABS |
|--|--|
| Color | Gray (Additional colors available – see Altelix.com) |
| Outer Dimensions (Height x Width x Depth) | 10.2 x 9.9 x 4.2 Inches (260 x 252 x 106 mm) |
| Inner Dimensions* (Height x Width x Depth) | 7.5 x 6.5 x 3.2 Inches (190 x 165 x 82 mm) |
| Mainlet | 4.5.11 (0.0.1.) |
| Weight | 1.5 lbs. (0.6 kg) |
| Ratings | 1.5 lbs. (0.6 kg) Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66 |
| | Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and |

^{*}Interior dimensions represent maximum space available for equipment.