



Features

- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets, Zip Ties, Cable Management Loops
- Optional Pole Mount Kit Available

Description

Weatherproof Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP120905** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

Complete with Cable Grommets and Wire Management Accessories

This enclosure includes 4 weatherproof cable grommets. Simply punch out the seal and run your cables. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, plastic wire management loops, door locking key and more.

Pole Mount Available

A pole mounting kit is also available for this enclosure. Attaches to the rear of the enclosure, it allows it to be mounted to poles and fence posts up to 9.5 inches in diameter.

Specifications

| | |
|---|--|
| Material | Polycarbonate + ABS |
| Color | Gray (Additional colors available – see Altelix.com) |
| Outer Dimensions (Height x Width x Depth) | 13.1 x 10.2 x 4.7 Inches (334 x 259 x 120 mm) |
| Inner Dimensions* (Height x Width x Depth) | 9.4 x 7.5 x 3.7 Inches (239 x 190 x 95 mm) |
| Weight | 1.9 lbs. (0.9 kg) |
| Ratings | Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66 |
| Flame Rating | Meets UL94-V0 |

*Interior dimensions represent maximum space available for equipment.