PORTACABS



.05" aluminum. Front panel recessed .50" and fits contour of cabinet. Louvered sides. Welded back has opening. Four plastic feet furnished.

BONUS FEATURES

Designed for bench or portable use. Lightweight yet strong. Reinforced flexible handle recessed to permit stacking. Carry handle limited to 25 Lb. load capacity.

FINISH

· Metallic Gray (MG).

Cata l og No.	Overall Size			Recommended			Louvers	Wqt
	Height	Width	Depth	Bud Chassis	Panel Space	Rear Opening	Per side	
WA-1540	8.00"	6.12"	8.00"	AC-402	$7.79^{\prime\prime}\times5.92^{\prime\prime}$	2.00" × 4.50"	1 Set	2.00
WA-1541	9,00″	8,12"	12,00″	AC-407	8.79" × 7.92"	2,00" × 6,50"	2 Sets	3,50
WA-1542	8.00″	10.12"	8.00″	AC-406	7.79" × 9.92"	2.00" × 8.50"	1 Set	3.75
WA-1543	11.00"	11.12″	18.00″	AC-416	10.79" × 10.92"	2.00" × 9.50"	3 Sets	5.50

SHEET METAL BOXES

NEMA 1 JUNCTION BOXES

WITH HINGED COVER

Catalog No. w/Knockouts	External Dimensions $H \times W \times D$	Wt. (Lbs.)	
JBH-4944-KO	6" × 4" × 3.5"		
JBH-4953-KO	6" × 4" × 4"	3	
JBH-4954-K0	6" × 6" × 3"	3	
JBH-4945-KO	6" × 6" × 3.5"		
JBH-4955-KO	6" × 6" × 4"	3	
JBH-4956-KO	8" × 6" × 4"	4	
JBH-4957-K0	8" × 8" × 4"	5	
JBH-4958-KO	10" × 8" × 4"	6	
JBH-4959-KO	10" × 8" × 6"	7	
JBH-4960-K0	10" × 10" × 4"	7	
JBH-4961-K0	10" × 10" × 6"	8	





Easy-open hinged cover for access to electrical wiring. Removable concentric knockouts on all four sides. Heavy-duty steel box for all types of industrial and commercial wiring.

DESIGN FEATURES

- Heavy duty 16 ga, welded steel construction
- Hinged cover with slotted head cam lock
- Easily removable concentric knockouts on all four sides for industry standard conduit sizes. 3" depth box does not have knockouts on hinge side.
- · Four wall mounting holes in back
- Embossed grounding hole in bottom allows easy access and flush wall mounting.
- · Complies with NEMA and UL-50 Type 1 rating
- UL listed

FINISH

• Durable ANSI 65 grey powder coating

SHEET METAL BOXES

NEMA 1 JUNCTION BOXES

For full dimensional information, see our Web site at www.budind.com.

WITH SCREW COVER

Catalog No. w/o Knockouts	Catalog No. w/Knockouts	External Dimensions H × W × D
JB-3950	JB-3950-KO	4" × 4" × 3"
JB-3951	JB-3951-K0	4" × 4" × 4"
JB-3952	JB-3952-K0	6" × 4" × 3"
JB-3944	JB-3944-KO	6" × 4" × 3.5"
JB-3953	JB-3953-K0	6" × 4" × 4"
JB-3954	JB-3954-KO	6" × 6" × 3"
JB-3945	JB-3945-KO	6" × 6" × 3.5"
JB-3955	JB-3955-KO	6" × 6" × 4"
JB-3956	JB-3956-KO	8" × 6" × 4"
JB-3957	JB-3957-KO	8" × 8" × 4"
JB-3958	JB-3958-KO	10" × 8" × 4"
JB-3959	JB-3959-KO	10" × 8" × 6"
JB-3960	JB-3960-K0	10" × 10" × 4"
JB-3961	JB-3961-K0	10" × 10" × 6"





Lift-off screw cover for easy access to electrical wiring. Embossed grounding hole in bottom allows flush wall mounting. Available with or without knockouts.

DESIGN FEATURES

- Heavy duty 16 ga. welded steel construction
- Screwed on flat cover with key holes for easy assembly
- Easily removable concentric knockouts on all four sides for industry standard conduit sizes
- Four wall mounting holes in back
- Embossed grounding hole in bottom allows flush wall mounting
- Complies with NEMA and UL-50 Type 1 rating
- UL listed

FINISH

Durable ANSI 65 grey powder coating