



*Quality Products. Service Excellence.*

## Type 4X Stainless Steel Two Door Floormount Enclosure *HN4 FM SS Series*

Continuous Hinge Door with Handle



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

### Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.
- 12" floor stands are welded to the enclosure.

### Standards


- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 13
  - IEC 60529, IP66

### Finish


- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable inner panel is finished in white powder coating.

### Accessories


- |                                      |  |
|--------------------------------------|--|
| • Ventilation                        | • Door Clamping Hardware               |
| • Door Stop Kit                      | • Drip Shield Kit                      |
| • Door Support Guide                 | • Type 1 Louvered Ventilating Plates   |
| • Wallmount Quick Release Clamp      | • Temperature Controls and Accessories |
| • Window Kits                        | • Inner Panels                         |
| • Ground Wire Kits                   | • Mechanical Interlock                 |
| • Barrier Kits for Type 4 Floormount |  |



FRONT VIEW



SECTION Y-Y



SECTION X-X

304 S.S. Part Number	316 S.S. Part Number	Overall A	Overall B	Overall C	Body Gauge	Panel Gauge	Inner Panel (Included)	
		A	B	C			D	E
HN4FM604812SS	HN4FM604812S16	60.13	48.06	12.69	12	10	56.00	44.00
HN4FM604818SS	HN4FM604818S16	60.13	48.06	18.69	12	10	56.00	44.00
HN4FM606012SS	HN4FM606012S16	60.13	60.06	12.69	12	10	56.00	56.00
HN4FM606018SS	HN4FM606018S16	60.13	60.06	18.69	12	10	56.00	56.00
HN4FM726012SS	HN4FM726012S16	72.13	60.06	12.69	12	10	68.00	56.00
HN4FM726018SS	HN4FM726018S16	72.13	60.06	18.69	12	10	68.00	56.00
HN4FM727212SS	HN4FM727212S16	72.13	72.06	12.69	12	10	68.00	68.00
HN4FM727218SS	HN4FM727218S16	72.13	72.06	18.69	12	10	68.00	68.00
HN4FM727224SS	HN4FM727224S16	72.13	72.06	24.69	12	10	68.00	68.00

10/14/2018

Type 4X Stainless Steel Two Door Floormount Enclosure (HN4 FM SS Series) - Hammond Mfg.

Tags: **HN4FM**

*Data subject to change without notice*

© 2018. Hammond Manufacturing Ltd. All rights reserved.