

Quality Products. Service Excellence.

Knockdown Stacking Rack Cabinet RCSC Series

1,500 lbs|680 kg Weight Capacity











Ideal for AV or IT/Server applications, the RCSC Rack Cabinet features a stacking design that allows for up to three (3) cabinets* to be stacked atop each other. This Rack Cabinet is fully loaded and includes two (2) pairs of infinitely adjustable sliding EIA square-hole rails, punch-outs for cable entry and/or fan cooling and comes in a variety of sizes and depths.

The unique stacking feature enables your cabinet space to grow as your needs do. *Stack up-to three (3) 12U, two (2) 24U or one (1) of each cabinet atop each other using the required **RCSCBAY** baying kit. The 12U cabinet is a great starter cabinet for any small to medium sized business.

Features

- · Constructed in 16-gauge steel.
- Includes two (2) pairs of infinitely adjustable 19" EIA-310-D compliant square-hole mounting rails with rack unit markings.
- Four (4) embosses are included with support for optional levelling feet or casters.
- · Grounding studs provided on body.
- The top and bottom of the RCSC includes two (2) laser knockouts (per side) for cableentry or fans (includes gasket strip material).
- Includes a laser knockout rear gland plate for floor-level cable entry.
- · Finished in rugged black powder paint.
- Ships unassembled in a flat pack container for easy handling and shipping protection.

Specifications

- Mounting rails are infinitely adjustable in depth and are fabricated of heavy duty 14-gauge steel, painted smooth black.
- Optional doors are available in solid, tinted acrylic with venting (see above-left) and high airflow vented.
 - Snap-in hinges can be mounted without having to bolt-on from inside the cabinet.
 In addition, the hinges can be mounted on the left or right.
- High airflow perforated doors for both front and rear of the cabinet are suggested for mos server applications.
 - Perforated doors meet server manufacturer Free-Air-Ratio (FAR) requirements at 63%
- For 36" depth cabinet side panels include cable entry knockouts.
- Tested to nearly double the suggested load rating of 1,500 lbs (680 kg).
- TAA Compliant.
- · RoHS Compliant.
- · Manufactured in North America.

Gallery















Accessories

- Universal Rack Shelf
- Rack Mount Locking Storage Drawer
- Sliding Keyboard Shelf
- Outlet Strips
- Adjustable Depth Cable Manager
- Horizontal Hinged Cable Manager
- Horizontal Steel Finger Cable Manager
- Cabinet Caster Set
- Leveling Feet

- Adjustable Depth 4-Post Rack Mount Shelf
- Four Post Mounting Sliding Shelf
- Mounting Screw and Cage Nut Combo-Pack
- Rack Unit Label
- Horizontal Lacing Strip
- Horizontal Ring Cable Manager
- Rack Panels
- Grounding
- Fan Kits

| | Overall Dimensions | | | Rack | Usable Mounting Dimensions | | |
|----------------|--------------------|-------|-------|-------|----------------------------|-------|-------|
| Part No. | Height | Width | Depth | Units | Height | Width | Depth |
| RCSC1902124BK1 | 25.00 | 24.00 | 24.50 | 12U | 21.00 | 19.00 | 22.99 |
| RCSC1902131BK1 | 25.00 | 24.00 | 31.50 | 12U | 21.00 | 19.00 | 29.99 |
| RCSC1902136BK1 | 25.00 | 24.00 | 36.00 | 12U | 21.00 | 19.00 | 29.99 |
| RCSC1904224BK1 | 46.00 | 24.00 | 24.50 | 24U | 42.00 | 19.00 | 22.99 |
| RCSC1904231BK1 | 46.00 | 24.00 | 31.50 | 24U | 42.00 | 19.00 | 29.99 |
| RCSC1904236BK1 | 46.00 | 24.00 | 36.00 | 24U | 42.00 | 19.00 | 29.99 |

Optional Doors

| Part No. | Part No. | Part No. | Use with | Use with Cabinet Panel Height | |
|----------------|----------------|--------------------|----------|-------------------------------|--|
| Solid Door | Vented Door | Vented Window Door | Units | Rack Units | |
| RCSC19021SDBK1 | RCSC19021VDBK1 | RCSC19021WDBK1 | 21.00 | 12U | |
| RCSC19042SDBK1 | RCSC19042VDBK1 | RCSC19042WDBK1 | 42.00 | 24U | |

RCSC Baying Kit

Part No. RCSCBAY

Tags: knock-down, knock down

Data subject to change without notice

© 2019. Hammond Manufacturing Ltd. All rights reserved.