



Specification



- Handle
Zinc die-cast
- Insert and screw
Steel, blackened
- Plastic coated
black, RAL 9005, textured finish
orange, RAL 2004, textured finish
red, RAL 3000, textured finish
silver, RAL 9006, textured finish
- chrome-plated
- uncoated
- ISO-Fundamental tolerances → page XYZ
- RoHS compliant

- SW
- OS
- RS
- SR
- CR
- RH

On request

- Call our sales staff for pricing and delivery on your special modification requirements.

Information

GN 300 Adjustable hand levers are the result of modern industrial design. All such levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations which can be easily be disengaged. Pulling the lever upwards, disengages the serrations, allowing it to be swivelled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

see also...

- *Stainless Steel Adjustable Lever GN 300.5 (with female thread) → page XYZ*
- *Zinc Die-Cast Adjustable Levers with Push Button GN 303 (with push button and female thread) → page XYZ*
- *Zinc Die-Cast Adjustable Levers GN 300 (with screw) → page XYZ*
- *Zinc Die-Cast Adjustable Levers GN 300.1 (with Stainless Steel-threaded bush) → page XYZ*
- *Adjustable Levers with Secure Clamping Force GN 300.4 (with increased clamping force and female thread) → page XYZ*
- *Straight Zinc Die-Cast Adjustable Levers GN 302 (with female thread) → page XYZ*

How to order	1	l ₁
	2	d ₁ (d ₂)
300-30-M3-SW	3	Color (Finish)

Metric table

Dimensions in: millimeters - *inches*

1 l_1	2 d_1 Thread			2 d_2 H7 Bore		d_3	d_4	h_1	h_2	h_3	h_4 Stroke	t min.
30 1.18	M 3	-	-	-	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14	7 .28
30 1.18	M 4	M 5	M 6	B 5	B 6	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14	9 .35
45 1.77	M 4	M 5	M 6	B 5	B 6	10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14	9 .35
63 2.48	M 6	M 8	-	B 8	-	13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16	11 .43
78 3.07	M 8	M 10	-	B 8	B 10	16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16	14 .55
92 3.62	M 10	M 12	-	B 12	-	19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16	17 .67
108 4.25	M 12	M 14	M 16	B 12	B 16	23 .91	30 1.18	50.5 1.99	12 .47	75 2.95	5 .20	22 .87

Inch table

Dimensions in: inches - *millimeters*

1 l_1	2 d_1 Thread			2 d_2 Bore		d_3	d_4	h_1	h_2	h_3	h_4 Stroke	t min.
1.18 30	10 x 32 10 x 32	10 x 24 10 x 24	1/4 x 20 1/4 x 20	B 1/4 B 1/4	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5	.35 9
1.77 45	10 x 32 10 x 32	10 x 24 10 x 24	1/4 x 20 1/4 x 20	B 1/4 B 1/4	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5	.35 9
2.48 63	1/4 x 20 1/4 x 20	5/16 x 18 5/16 x 18	-	B 1/4 B 1/4	B 5/16 B 5/16	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4	.43 11
3.07 78	5/16 x 18 5/16 x 18	3/8 x 16 3/8 x 16	-	B 5/16 B 5/16	B 3/8 B 3/8	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4	.55 14
3.62 92	3/8 x 16 3/8 x 16	1/2 x 13 1/2 x 13	-	B 3/8 B 3/8	B 1/2 B 1/2	.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4	.67 17
4.25 108	1/2 x 13 1/2 x 13	5/8 x 11 5/8 x 11	-	B 1/2 B 1/2	B 5/8 B 5/8	.91 23	1.18 30	1.99 50.5	.47 12	2.95 75	.20 5	.87 22