



**Metric table**

Dimensions in: millimeters - inches

| d <sub>1</sub> | Length l ±0.5 |        | d <sub>2</sub><br>Thread | d <sub>3</sub> | h    | r   | t<br>min. |
|----------------|---------------|--------|--------------------------|----------------|------|-----|-----------|
|                | mm            | inches |                          |                |      |     |           |
| 12             | 125           | 160    | M 5                      | 12.8           | 51   | 14  | 12        |
| .47            | 4.92          | 6.30   |                          | .50            | 2.01 | .55 | .47       |
| 16             | 160           | 200    | M 6                      | 16.8           | 59   | 18  | 12        |
| .63            | 6.30          | 7.87   |                          | .66            | 2.32 | .71 | .47       |

**Specification**

- **Stainless steel** **A4**  
European Standard No. 1.4404 (AISI 316L)
  - Matte finish (Ra < 0.8 µm) **MT**
  - Polished finish (Ra < 0.8 µm) **PL**
- **Sealing ring**  
Hydrogenated acrylonitrile butadiene rubber (H-NBR)
  - Blue
  - Temperature resistant from -13 °F to +302 °F (-25 °C to +150 °C)
  - Hardness 85 ±5 shore A
  - FDA compliant
- **RoHS compliant**

**Information**

GN 429 cabinet “U” handles are intended for use in hygiene areas. The sealed mounting surfaces enable fastening without dead spaces. The high quality finish prevents adherence of dirt and facilitates cleaning.

The manufacturing process (bending) allows the production of special lengths in relatively small quantities.

*see also...*

- *Product Range [Hygienic Design](#)*
- *Sealing Rings GN 7600 ([Hygienic Design](#))*

**On request**

- Special lengths

| How to order |                                |
|--------------|--------------------------------|
| 1            | Material                       |
| 2            | Handle diameter d <sub>1</sub> |
| 3            | Length l                       |
| 4            | Finish                         |

1 2 3 4  
**GN 429-A4-12-160-MT**