



Metric



Metric table

1

2

Dimensions in: millimeters - inches

$d_1 -0.5$	$l_1 +2$	a_1	a_2	d_2	h_1	$h_2 -0.1$	l_2
30 1.18	100 3.94	18 .71	9 .35	32 1.26	34.5 1.36	14.5 .57	106 4.17
30 1.18	200 7.87	18 .71	9 .35	32 1.26	34.5 1.36	14.5 .57	206 8.11
30 1.18	300 11.81	18 .71	9 .35	32 1.26	34.5 1.36	14.5 .57	306 12.05
30 1.18	400 15.75	18 .71	9 .35	32 1.26	34.5 1.36	14.5 .57	406 15.98
30 1.18	500 19.69	18 .71	9 .35	32 1.26	34.5 1.36	14.5 .57	506 19.92

Specification

3

- Tube extrusion
Aluminum
 - Black, RAL 9005, textured finish
 - Anodized finish, natural color

● SW
● EL

- End caps
Zinc die-cast, powder coated
Black, RAL 9005, textured finish

- Countersunk screws
 - Self-tapping, with internal Torx® drive
 - Black zinc plated

- RoHS compliant

On request

- Powder coated end caps, silver, textured finish
- Special lengths
- Various metric size fasteners and kit packaging

Information

GN 481 edge handles are particularly compact and are used, for example, on the side of monitor housings as a handling aid or generally to protect the edges of housings.

Tolerance compensation of 1 mm per end cap simplifies installation. The two end caps are mounted to the handle profile with self-tapping countersunk screws so they can be screwed back on after adjusting the length of the handle without requiring readjustment. This allows the length of the housing to be adapted to any desired size.

How to order

1 2 3
GN 481-30-300-SW

1 Handle diameter d_1 2 Length l_1

3 Finish