



SS Stainless Steel

3 Type

- A** Mounting from the back (tapped blind hole)
- B** Mounting from the operator's side

Metric table

Dimensions in: millimeters - inches

1 b		2 l₁ ±0.25	l₂ ≈	a	d₁	d₂	h₁	h₂	t₁ min.	t₂
GN 565.4	GN 565.9				Type A	Type B				
20	20	160	185	13	M 6	5.3	50	5	8	5
.79	.79	6.30	7.28	.51		.21	1.97	.20	.31	.20
20	20	192	221	13	M 6	5.3	50	5	8	5
.79	.79	7.56	8.70	.51		.21	1.97	.20	.31	.20
26		160	190	17	M 8	6.4	57	6	11	6
1.02		6.30	7.48	.67		.25	2.24	.24	.43	.24
26		192	227	17	M 8	6.4	57	6	11	6
1.02		7.56	8.94	.67		.25	2.24	.24	.43	.24

Specification

• GN 565.4

- Aluminum
- Powder coated
- Black, RAL 9005, textured finish
- Red, RAL 3000, textured finish
- Silver, RAL 9006, textured finish
- Anodized finish, natural color
- Blank, tumbled finish

- **SW**
- **RS**
- **SR**
- **EL**
- **BL**

• GN 565.9

- Stainless steel
- European Standard No. 1.4301 (AISI 304)
- Matte, shot-blasted finish

- **MT**

• RoHS compliant

Information

GN 565.4 and GN 565.9 arched pull handles are preferably used for such applications where easy sliding of folding doors or cabinet drawers can be operated with a single finger. Their shape blends well with modern design.

The manufacturing process allows the production of special lengths in relatively small quantities.

see also...

- *Arched Pull Handles GN 665 (Aluminum, Ellipse Shaped Profile)*
- *Arched Pull Handles GN 424.1 / GN 424.5 (Steel / Stainless Steel, Ø 10 mm)*

On request

- Special lengths
- Various metric size fasteners and kit packaging

How to order (Aluminum)	1 Handle width b
1 2 3 4	2 Length l₁
GN 565.4-20-160-B-RS	3 Type
	4 Finish

How to order (Stainless steel)	1 Handle width b
1 2 3 4	2 Length l₁
GN 565.9-20-192-A-MT	3 Type
	4 Finish

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

