



SS Stainless Steel

**Specification**



- Tube Ø 30x1.5 mm  
Aluminum / stainless steel
  - Handle legs / covers  
Plastic (Polyamide PA)  
- Glass fiber reinforced  
- Temperature resistant up to 212 °F (100 °C)
  - Tube ● SW  
Aluminum, powder coated  
Black, RAL 9005, textured finish  
Handle legs / covers  
Black, matte finish
  - Tube ● EL  
Aluminum  
Anodized finish, natural color  
Handle legs / covers  
Black, matte finish
  - Tube ● ELG  
Aluminum  
Anodized finish, natural color  
Handle legs / covers  
Light gray, matte finish
  - Tube ● NG  
Stainless steel  
European Standard No. 1.4301 (AISI 304)  
Ground, matte glossy finish  
Handle legs / covers  
Black, matte finish
- RoHS compliant

**Information**

GN 666.1 tubular grip handles offer an even more extensive size range for virtually any application that requires mounting from the top side.

see also...

- *Tubular Grip Handles GN 666.7 (Stainless Steel, with Threaded Studs)*

**On request**

- Various inch and metric size fasteners and kit packaging

<p>How to order (Inch, aluminum tube)</p> <p style="text-align: center;"> <span style="color: red;">1</span> <span style="color: red;">2</span> <span style="color: red;">3</span> <span style="color: red;">4</span> </p> <p style="font-size: 1.2em; font-weight: bold;">GN 666.1-1.18-5/16X18-8.00-EL</p>	<p>1 Handle diameter <math>d_1</math></p> <p>2 Thread <math>d_2</math></p> <p>3 Length <math>l_1</math></p> <p>4 Material / finish</p>
<p>How to order (Metric, stainless steel tube)</p> <p style="text-align: center;"> <span style="color: red;">1</span> <span style="color: red;">2</span> <span style="color: red;">3</span> <span style="color: red;">4</span> </p> <p style="font-size: 1.2em; font-weight: bold;">GN 666.1-30-M8-400-NG</p>	<p>1 Handle diameter <math>d_1</math></p> <p>2 Length <math>l_1</math></p> <p>3 Material / finish</p>

**Inch table**

Dimensions in: inches - *millimeters*

<b>1</b> d <sub>1</sub>	<b>2</b> d <sub>2</sub> Thread	<b>3</b> l <sub>1</sub> ±0.02	b	h	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub>
1.18 30.0	5/16 x 18	8.00 203.2	.71 18.0	2.36 59.9	9.18 233.2	6.82 173.2	9.38 238.3	3.5 88.9	.82 20.8
1.18 30.0	5/16 x 18	10.00 254.0	.71 18.0	2.36 59.9	11.18 284.0	8.82 224.0	11.38 289.1	3.5 88.9	.82 20.8
1.18 30.0	5/16 x 18	12.00 304.8	.71 18.0	2.36 59.9	13.18 334.8	10.82 274.8	13.38 339.9	3.5 88.9	.82 20.8
1.18 30.0	5/16 x 18	16.00 406.4	.71 18.0	2.36 59.9	17.18 436.4	14.82 376.4	17.38 441.5	3.5 88.9	.82 20.8
1.18 30.0	5/16 x 18	20.00 508.0	.71 18.0	2.36 59.9	21.18 538.0	18.82 478.0	21.38 543.1	3.5 88.9	.82 20.8
1.18 30.0	5/16 x 18	24.00 609.6	.71 18.0	2.36 59.9	25.18 639.6	22.82 579.6	25.38 644.7	3.5 88.9	.82 20.8

**Metric table**

Dimensions in: millimeters - *inches*

<b>1</b> d <sub>1</sub>	<b>2</b> d <sub>2</sub> Thread	<b>3</b> l <sub>1</sub> ±0.5	b	h	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub>
30 1.18	M 8	200 7.87	18 .71	60 2.36	230 9.06	170 6.69	265 10.43	85 3.35	17 .67
30 1.18	M 8	250 9.84	18 .71	60 2.36	280 11.02	220 8.66	315 12.40	85 3.35	17 .67
30 1.18	M 8	300 11.81	18 .71	60 2.36	330 12.99	270 10.63	365 14.37	85 3.35	17 .67
30 1.18	M 8	400 15.75	18 .71	60 2.36	430 16.93	370 14.57	465 18.31	85 3.35	17 .67
30 1.18	M 8	500 19.69	18 .71	60 2.36	530 20.87	470 18.50	565 22.24	85 3.35	17 .67
30 1.18	M 8	600 23.62	18 .71	60 2.36	630 24.80	570 22.44	665 26.18	85 3.35	17 .67

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4

