



Specification



- Tube Ø 20x1.5 mm / Ø 30x1.5 mm
Aluminum
 - Powder coated
 - Black, RAL 9005, textured finish **● SW**
 - Anodized finish, natural color **● EL**
- Stainless steel
 - European Standard No. 1.4301 (AISI 304)
 - Ground, matte glossy finish **● NG**
- Handle legs
 - Plastic
 - Technopolymer (Polyamide PA)
 - Glass fiber reinforced
 - Temperature resistant up to 212 °F (100 °C)
 - Black, matte finish
- Socket cap screws DIN 912
 - Hexagon nuts ISO 4032
 - Washers DIN 125
 - Stainless steel
 - European Standard No. 1.4301 (AISI 304)

• RoHS compliant

Information

GN 667 tubular grip handles are very versatile, because special lengths of handles can be ordered complete in smaller quantities.

If desired, handle legs may be ordered individually to make your own special length of handle.

see also...

- Product Range Standard Parts for Profile Systems
- Ergostyle® Tubular Handles EN 767 (Powder Coated Tube)
- Ergostyle® Tubular Handles EN 767.1 (Anodized Tube)
- T-Nut Assemblies GN 965 (for 30 / 40 mm T-Slot Profile Systems)
- T-Nut Assemblies GN 968 (for 30 / 40 / 45 mm T-Slot Profile Systems)

On request

- Special lengths
- Supports for handles with longer spans or greater loads
- Various metric size fasteners and kit packaging

<p>How to order (Aluminum tube)</p> <p>GN 667-20-200-EL</p>	<p>1 Handle diameter d₁</p> <p>2 Length l₁</p> <p>3 Finish</p>
<p>How to order (Stainless steel tube)</p> <p>GN 667-30-1000-NG</p>	<p>1 Handle diameter d₁</p> <p>2 Length l₁</p> <p>3 Finish</p>

Metric table

Dimensions in: millimeters - inches

¹ d ₁	² l ₁ ±1	a	b	d ₂ Thread	h ₁	h ₂	l ₂	l ₃	l ₄	l ₅ max.	l ₆
20 .79	180 7.09	48 1.89	28 1.10	M 8	45 1.77	58 2.28	200 7.87	142 5.59	25 .98	6 .24	9.5 .37
20 .79	200 7.87	48 1.89	28 1.10	M 8	45 1.77	58 2.28	220 8.66	162 6.38	25 .98	6 .24	9.5 .37
20 .79	250 9.84	48 1.89	28 1.10	M 8	45 1.77	58 2.28	270 10.63	212 8.35	25 .98	6 .24	9.5 .37
20 .79	300 11.81	48 1.89	28 1.10	M 8	45 1.77	58 2.28	320 12.60	262 10.31	25 .98	6 .24	9.5 .37
20 .79	350 13.78	48 1.89	28 1.10	M 8	45 1.77	58 2.28	370 14.57	312 12.28	25 .98	6 .24	9.5 .37
20 .79	400 15.75	48 1.89	28 1.10	M 8	45 1.77	58 2.28	420 16.54	362 14.25	25 .98	6 .24	9.5 .37
30 1.18	300 11.81	57 2.24	38 1.50	M 10	60 2.36	78 3.07	324 12.76	254 10.00	35 1.38	9 .35	14.5 .57
30 1.18	350 13.78	57 2.24	38 1.50	M 10	60 2.36	78 3.07	374 14.72	304 11.97	35 1.38	9 .35	14.5 .57
30 1.18	400 15.75	57 2.24	38 1.50	M 10	60 2.36	78 3.07	424 16.69	354 13.94	35 1.38	9 .35	14.5 .57
30 1.18	500 19.69	57 2.24	38 1.50	M 10	60 2.36	78 3.07	524 20.63	454 17.87	35 1.38	9 .35	14.5 .57
30 1.18	600 23.62	57 2.24	38 1.50	M 10	60 2.36	78 3.07	624 24.57	554 21.81	35 1.38	9 .35	14.5 .57
30 1.18	700 27.56	57 2.24	38 1.50	M 10	60 2.36	78 3.07	724 28.50	654 25.75	35 1.38	9 .35	14.5 .57
30 1.18	1000 39.37	57 2.24	38 1.50	M 10	60 2.36	78 3.07	1024 40.31	954 37.56	35 1.38	9 .35	14.5 .57

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4