


LED MULTI-FUNCTION LIGHT

Quadro-LED-HI



Designed for tough requirements under industrial conditions.

- Innovative LED light with high signaling effect.
- Suitable for indoor and outdoor use.
- Extremely insensitive to shock and vibration.
- 3 selectable operating modes as standard:
 - Continuous light
 - Blinking light
 - Flashing light
- 24 V AC/DC devices as standard with Soft Start Module.
- Double-pole terminal.
- Inexpensive and flexible; wide range power supplies as standard.



protection system



impact-proof housing



operating temperature




brightness adjustable



warranty



PRODUCT	Quadro-LED-HI		
---------	---------------	--	--

DATA			
Rated voltage	115/230 V		24 V
	AC 50 60 Hz / DC		DC
Operating range	90–253 V		11–60 V
Current consumption (@ 1 Hz flash)	45 mA @ 230 V AC		165 mA @ 24 V DC
Operating mode internally and externally selectable (DC)	continuous light	blinking light	flashing light
Light alternation frequency		1 Hz / 2 Hz	0.1 Hz / 0.5 Hz / 0.75 Hz / 1 Hz / 2 Hz
Light source	4 high output LED		
Light intensity (DIN 5037) ¹	75 cd (reducible)		
Max. viewing distance	201 m		
Operating temperature	–40 °C ... +55 °C		
Storage temperature	–40 °C ... +70 °C		
Relative humidity	100 %		
Protection system (EN 60529)	IP 66 IP 67		
Impact resistance (EN 50102)	IK08		
Protection class	II		
Service life of the light source	≥50,000 hrs		
Material	lens	 polycarbonate (PC)	
	housing	polycarbonate (PC), grey RAL 7035	
Cable entry	2x M20/M32 sideways, 2x M20 bottom side		
Connecting terminal	cage clamp 0.08–2.5 mm ² (2 per Pol)		
Weight	500 g		

¹ with a clear lens