

DESK CONSOLES

Application

Intended for indoor use to provide a degree of protection to personnel against access to hazardous parts, also to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects and falling dirt, to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water, splashing water. Designed for use in a standing or sitting position with single or dual access and top that opens for easy accessibility. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction

- 0.075" carbon steel.
- Seams continuously welded and ground smooth.
- 25 degree Sloped top.
- Door props on sloped door to hold in the open position.
- Pour in place oil and water resistant gasket.
- Flange trough collar around all sides of door opening.
- Concealed hinges.
- Removable doors.
- Removable print pocket.
- Ground studs on door and body.
- Rubber pads with provision for leveling pads on bottom of enclosure.
- Black quarter turn latches on top door.
- Keylocking black 3-point flush swing handle in front door of single access, front and rear doors on dual access.
- Mounting studs welded on interior back for mounting optional sub-panels on single access console.
- Mounting channels welded on sides of interior body for mounting optional sub-panels on dual access console.
- Mounting hardware included for (1) optional sub-panel.

Finish

ANSI-61 gray powder coated inside and out. Optional panels are powder coated white.

Options

Optional tamper-resistant inserts or padlocking handles are available.

IS3 Industry Standards

NEMA Type 3R, 12 & Type 13
 UL Listed Type 3R & 12
 CSA Type 3R & 12
 IEC 60529 IP55

IS4 Industry Standards

NEMA Type 3R, 4, 12 & Type 13
 UL Listed Type 3R, 4 & 12
 CSA Type 3R, 4 & 12
 IEC 60529 IP66

***To maintain Type 3R listing, Drainage is required. Install equally rated drainage device or drill a 1/8 to 1/4 inch hole in the bottom center of the enclosure, approximately 1 inch from the right, and 1 inch from the left for drainage, use listed rain-tight or wet location hubs.

28

DESK CONSOLES

Enclosure Product Code C1

Sub-Panel (P3)

Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	Catalog No.	Panel Height (D)	Panel Width (E)
Single Access Single-Door							
SCE-402516SDC	40.25	25.25	15.50	IS4	SCE-30P24	27.00	21.00
SCE-403716SDC	40.25	37.25	15.50	IS3	SCE-36P30	33.00	27.00
SCE-462519SDC	46.25	25.25	18.50	IS4	SCE-36P24	33.00	21.00
SCE-463719SDC	46.25	37.25	18.50	IS3	SCE-36P36	33.00	33.00
Dual Access Single-Door							
SCE-462519DC	46.25	25.25	18.50	IS4	SCE-36P24	33.00	21.00
SCE-463719DC	46.25	37.25	18.50	IS3	SCE-36P36	33.00	33.00
Single Access Overlapping Two-Door							
SCE-464919SDC	46.25	49.25	18.50	IS3	SCE-48P36	45.00	33.00
SCE-466019SDC	46.25	59.88	18.50	IS3	SCE-60PC36	55.63	33.00
Dual Access Overlapping Two-Door							
SCE-464919DC	46.25	49.25	18.50	IS3	SCE-48P36	45.00	33.00
SCE-466019DC	46.25	59.88	18.50	IS3	SCE-60PC36	55.63	33.00
Dual Access Two-Door With Center Channel							
SCE-464919DCC	46.25	49.25	18.50	IS4	SCE-48P36	45.00	33.00
SCE-466019DCC	46.25	59.88	18.50	IS4	SCE-60PC36	55.63	33.00

