

# ENVIRO-THERM® THERMAL MANAGEMENT

## FAN HEATER WITH THERMOSTAT

Designed to protect electrical controls, instruments and sensitive components from low temperatures and the effects of condensation and corrosion by maintaining a stable temperature within the electrical enclosure. These heaters are not intended for use in hazardous, wet, dusty or dirty locations. For installation information, consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

**IS24 - Industry Standards**  
UL Component Recognized

Catalog No.	Watt @ 60 Hz	Volt	Height	Width	Depth	Product Code
<a href="#">SCE-HF1251A</a>	125	115	5.50	4.00	4.50	P1
<a href="#">SCE-HF1252A</a>	125	230	5.50	4.00	4.50	P1
<a href="#">SCE-HF2001A</a>	200	115	5.50	4.00	4.50	P1
<a href="#">SCE-HF2002A</a>	200	230	5.50	4.00	4.50	P1
<a href="#">SCE-HF4001B</a>	400	115	7.50	4.00	4.50	P1
<a href="#">SCE-HF4002B</a>	400	230	7.50	4.00	4.50	P1
<a href="#">SCE-HF8001B</a>	800	115	7.50	4.00	4.50	P1
<a href="#">SCE-HF8002B</a>	800	230	7.50	4.00	4.50	P1



- Brushed Aluminum Housing
- Thermostat Range 0° to 100°F (-18° to 38°C)
- Heat discharge at the top of the heater
- Panel mount
- Air volume of 16 CFM on 125 & 200 Watt heaters, 26 CFM on 400 & 800 Watt heaters
- Heat indicator light
- Switch for Auto or Fan
- UL Recognized
- CSA Approved
- CE

## FAN HEATER

Compact design that heats up dynamically and is quiet during operation. Din rail clip design for 15mm, 35mm and C-Din Rail. 14" heater cable, 10" fan cable. 100 - 240V 50/60 Hz Heater and 24 V Integrated fan. For installation information, consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

**IS24 - Industry Standards**  
UL Component Recognized

Catalog No.	Watts	Max Current	Height	Width	Depth	Product Code
<a href="#">SCE-H350</a>	350	3.0 A	3.10	2.10	3.30	P1



## TOUCH SAFE HEATER

PTC (Positive Temperature Coefficient) Din rail clip design for 35mm Din Rail. Designed for protection from low temperatures, condensation and corrosion. Touch Safe with 2 screw terminal for standard AWG 14 wire. 110 - 240V AC or DC. For installation information, consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

**IS24 - Industry Standards**  
UL Component Recognized

Catalog No.	Watts	Max Current	Height	Width	Depth	Product Code
<a href="#">SCE-TSH25</a>	25	2.5 A	4.92	1.61	1.61	P1
<a href="#">SCE-TSH50</a>	50	3.5 A	4.92	1.61	1.61	P1
<a href="#">SCE-TSH75</a>	75	4.0 A	5.51	2.76	2.48	P1
<a href="#">SCE-TSH100</a>	100	5.0 A	5.51	2.76	2.48	P1
<a href="#">SCE-TSH150</a>	150	9.5 A	8.66	2.76	2.48	P1

