

Extra Large 30.5 mm Hinged Pushbutton Enclosures

Application -

Designed to offer protection for oil-tight pushbuttons, switches, and pilot lights from dust, water, dirt and oil. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.063" carbon steel.
- Continuously welded seams.
- Captivated cover screws thread into sealed wells.
- 4-way pushbutton holes accept all brands of oil-tight pushbuttons, switches and pilot lights. Hole diameter is 1.20" (30.5 mm).
- Oil-resistant gasket.
- Provisions for sub-panel.
- Ground stud on door and body.
- Bolt-on continuous hinge with stainless steel hinge pin.
- Welded mounting provision top and bottom of back.

Finish -

ANSI-61 gray powder coated inside and out. Optional sub-panels powder coated white.


IS2 - Industry Standards -

NEMA Type 4, 12 & Type 13
 UL Listed Type 4 & 12
 CSA Type 4 & 12
 IEC 60529 IP66




EXTRA LARGE 30.5 mm HINGED PUSHBUTTON ENCLOSURES


ENCLOSURE PRODUCT CODE A1						SUB-PANEL (P3)			
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	List Price	Catalog No.	Panel Height (D)	Panel Width (E)	List Price
SCE-4SPBH	8.13	8.00	6.00	IS2	107.08	SCE-8P8	7.00	7.00	4.89
SCE-6PBH	10.13	8.00	6.00	IS2	122.63	SCE-10P8	9.00	7.00	5.70
SCE-9PBH	10.13	10.00	6.00	IS2	142.99	SCE-10P10	9.00	9.00	6.73
SCE-12PBH	12.13	10.00	6.00	IS2	162.14	SCE-12P10	11.00	9.00	7.72
SCE-16PBH	12.13	12.00	6.00	IS2	184.70	SCE-12P12	11.00	11.00	9.08




SCE-4SPBH




SCE-6PBH



SCE-9PBH



SCE-12PBH



SCE-16PBH

Phone (989) 799-6871
 Fax (989) 799-4524



1 Operator System Enclosures
 2 Wall-Mount Enclosures
 3 Free-Standing & Floor-Mounted Enclosures
 4 Modular Enclosures
 5 Operator System Enclosures (Stainless Steel)
 6 Wall-Mount Enclosures (Stainless Steel)
 7 Free-Standing & Floor-Mounted Enclosures (Stainless Steel)
 8 Non-Metallic Enclosures
 9 Accessories
 10 Technical Information
 11 Index

EXTRA LARGE 30.5 mm HINGED PUSHBUTTON ENCLOSURES TECHNICAL DATA

